



Chemical resistance

Chemical Resistance A - F

Reagent	LDPE	HDPE	PP	PMP	PVC	PC	PS	SAN	ABS	ACRYLIC	PTFE	PFA	E-CTFE
Temperature °C	20 68	50 122	20 68										
Temperature °F													
Acetaldehyde	●	●	●	●	●	●	●	●	●	●	●	●	●
Acetic Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
Acetic Anhydride	●	●	●	●	●	●	●	●	●	●	●	●	●
Acetone	●	●	●	●	●	●	●	●	●	●	●	●	●
Acetyl Chloride	●	●	●	●	●	●	●	●	●	●	●	●	●
Ammonium Chloride (10%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Ammonium Hydroxide (28%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Amyl Acetate	●	●	●	●	●	●	●	●	●	●	●	●	●
Aniline	●	●	●	●	●	●	●	●	●	●	●	●	●
Aqua Regia	●	●	●	●	●	●	●	●	●	●	●	●	●
Benzaldehyde	●	●	●	●	●	●	●	●	●	●	●	●	●
Benzene	●	●	●	●	●	●	●	●	●	●	●	●	●
Benzoic Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
Boric Acid (10%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Bromine Gas (Dry)	●	●	●	●	●	●	●	●	●	●	●	●	●
Bromine Water	●	●	●	●	●	●	●	●	●	●	●	●	●
Butyl Acetate	●	●	●	●	●	●	●	●	●	●	●	●	●
Butyl Alcohol	●	●	●	●	●	●	●	●	●	●	●	●	●
Butyric Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
Calcium Hydroxide (Saturated)	●	●	●	●	●	●	●	●	●	●	●	●	●
Carbon Disulphide	●	●	●	●	●	●	●	●	●	●	●	●	●
Carbon Tetrachloride	●	●	●	●	●	●	●	●	●	●	●	●	●
Chlorine Gas (Dry)	●	●	●	●	●	●	●	●	●	●	●	●	●
Chlorine Water	●	●	●	●	●	●	●	●	●	●	●	●	●
Chloroform	●	●	●	●	●	●	●	●	●	●	●	●	●
Citric Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
m-Cresol	●	●	●	●	●	●	●	●	●	●	●	●	●
Cyclohexane	●	●	●	●	●	●	●	●	●	●	●	●	●
Dibutylphthalate	●	●	●	●	●	●	●	●	●	●	●	●	●
p-Dichlorobenzene	●	●	●	●	●	●	●	●	●	●	●	●	●
Diethyl Ether	●	●	●	●	●	●	●	●	●	●	●	●	●
Diethylene Glycol	●	●	●	●	●	●	●	●	●	●	●	●	●
Dimethyl Formamide	●	●	●	●	●	●	●	●	●	●	●	●	●
Dioxane	●	●	●	●	●	●	●	●	●	●	●	●	●
Ethyl Acetate	●	●	●	●	●	●	●	●	●	●	●	●	●
Ethyl Alcohol	●	●	●	●	●	●	●	●	●	●	●	●	●
Ethyl Chloride	●	●	●	●	●	●	●	●	●	●	●	●	●
Ethylene Chloride	●	●	●	●	●	●	●	●	●	●	●	●	●
Ethyl Oxide	●	●	●	●	●	●	●	●	●	●	●	●	●
Fluorine Gas (Dry)	●	●	●	●	●	●	●	●	●	●	●	●	●
Formaldehyde (Formalin)	●	●	●	●	●	●	●	●	●	●	●	●	●
Formic Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
Fuel Oil	●	●	●	●	●	●	●	●	●	●	●	●	●

This chart gives general guidelines only on the chemical resistance of plastics. There are many factors which influence chemical resistance - always test for your own application before selecting the appropriate product. If you have any doubts, please contact our Technical Department for advice.



Chemical Resistance G - Z

Reagent	LDPE	HDPE	PP	PMP	PVC	PC	PS	SAN	ABS	ACRYLIC	PTFE	PFA	E-CTFE
Temperature °C	20	50	20	50	20	50	20	50	20	50	20	50	20
Temperature °F	68	122	68	122	68	122	68	122	68	122	68	122	68
Glycerine (Glycerol)	●	●	●	●	●	●	●	●	●	●	●	●	●
Hexane	○	●	●	○	○	●	●	●	●	●	●	●	●
Hydrobromic Acid (25%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Hydrobromic Acid (35%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Hydrofluoric Acid (35%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Hydrogen Peroxide (30%)	●	○	●	●	●	●	●	●	●	●	●	●	●
Lactic Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
Methyl Acetate	●	●	●	●	●	●	●	●	●	●	●	●	●
Methyl Alcohol	●	●	●	●	●	●	●	●	●	●	●	●	●
Methyl Ethyl Ketone	●	○	●	●	●	●	●	●	●	●	●	●	●
Methylene Chloride	○	●	●	●	●	●	●	●	●	●	●	●	●
Mineral Oil	○	●	●	●	●	●	●	●	●	●	●	●	●
Naphthalene	○	●	●	●	●	●	●	●	●	●	●	●	●
Nitric Acid (10%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Nitric Acid (70%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Nitrobenzene	●	●	●	●	●	●	●	●	●	●	●	●	●
Oleum	●	●	●	●	●	●	●	●	●	●	●	●	●
Oxalic Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
Perchloric Acid (20%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Petrol	○	●	●	●	●	●	●	●	●	●	●	●	●
Petroleum Ether	○	●	●	●	●	●	●	●	●	●	●	●	●
Phosphoric Acid (85%)	●	○	●	●	●	●	●	●	●	●	●	●	●
Photographic Developer	●	●	●	●	●	●	●	●	●	●	●	●	●
Photographic Fixer	●	●	●	●	●	●	●	●	●	●	●	●	●
Potassium Hydroxide (50%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Potassium Permanganate (20%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Propylene Glycol	●	●	●	●	●	●	●	●	●	●	●	●	●
Pyridine	●	●	●	●	●	●	●	●	●	●	●	●	●
Salicylic Acid	●	●	●	●	●	●	●	●	●	●	●	●	●
Silver Nitrate	●	○	●	●	●	●	●	●	●	●	●	●	●
Sodium Hydroxide (50%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Sodium Hypochlorite (20%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Sodium Thiosulphate	●	●	●	●	●	●	●	●	●	●	●	●	●
Sulphuric Acid (10%)	●	●	●	●	●	●	●	●	●	●	●	●	●
Sulphuric Acid (98%)	○	●	●	●	●	●	●	●	●	●	●	●	●
Tetrahydrofuran	○	●	●	●	●	●	●	●	●	●	●	●	●
Tetrahydronaphthalene	●	●	●	●	●	●	●	●	●	●	●	●	●
Thionyl Chloride	●	●	●	●	●	●	●	●	●	●	●	●	●
Toluene	●	●	●	●	●	●	●	●	●	●	●	●	●
Trichloroethylene	●	●	●	●	●	●	●	●	●	●	●	●	●
Turpentine	●	●	●	●	●	●	●	●	●	●	●	●	●
Vegetable Oil	●	●	●	●	●	●	●	●	●	●	●	●	●
Xylene	●	●	●	●	●	●	●	●	●	●	●	●	●

Swisstrax
 S.A.S. au capital de 632 500 Euros
 8 Rue neuve 60400 CRISOLLES
 NAF : 4690Z